FICHE TECHNIQUE



Batterie Powercap® Active

Défault / CAU340-001-100



DESCRIPTION

The new PowerBoxTM1 battery pack features a micro USB connection for simpler, faster charging. A built-in fuel gauge reports battery level on demand. The charging cable connects directly to the battery pack, reducing the number of parts by removing the dock station used with the original PowerBoxTM. PowerBoxTM1 is compatible with all PowerCap® ActiveTM and PowerCap® ActiveTM IP units.

OPTIONS

Défault (CAU340-001-100)















INFORMATIONS TECHNIQUES



Pièces détachées

Batterie:

Type de batterie Li-ion

4000mAh, 3.7V, 14.8Wh

Micro USB 5VDC, 1.0A

4.2VDC, 3.4A

8+ hours

5 hours approx.



Poids du produit 120g

CARACTÉRISTIQUES



Powered Air

Protection to EN 12941 TH1P provides a cooling, comfortable supply of filtered air at 160 litres per minute, eliminating breathing resistance and visor misting.



Casquette anti-heurts

The cap uses JSP HardCap™ A1+ bump cap technology, exceeding the EN 812 standard. The cap cover is easily removable, wipeable and machine washable.



Micro USB Charging

PowerCap® Active™ is supplied with a micro USB cable for recharging in as little as 5 hours. The PowerBox[™]1 battery pack features a built-in fuel gauge, making it easy to check charge level.



Micro USB charging

PowerBox[™]1 supports micro USB charging, allowing battery packs to be charged using a range of power sources in as little as 5 hours. Simply connect the supplied cable directly to the PowerBox[™]1 pack to recharge.



Built-in fuel gauge

LED indicators on the PowerBox™1 enable visual identification of charge level. Green, amber and red lights provide feedback on battery life, making it easy to confirm when recharging is required for safer working with less downtime.



PowerCable connection

The new battery pack is connected to the respirator unit via the same connection as the original PowerBox™. Existing batteries can continue to be used and switching to the PowerBox[™]1 is effortless with no extra parts required.

GAMME



TÉLÉCHARGEMENTS

Pack d'images (ZIP)

doc-powercap active.pdf (PDF)







Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com





